



ADHESIVES & COATINGS, INC
QURETECH®
TECHNICAL DATA SHEET

Country Club Road, PO Box 628
Grafton, WV 26354
800-847-7773
Fax: 304-265-5202
www.dyna-techadhesives.com
www.quiretech.com

Providing Advanced Water-based and Energy
Curable Coatings and Adhesives
For Over 25 Years.
Clean, Safe, Worker Friendly

SureTac 2092

80°C Hydrocarbon Resin Emulsion

A solvent-free waterborne emulsion of hydrocarbon resin, formulated for tackifying various latex polymers. This emulsion is acid stable and has been formulated to be a replacement for commercially available hydrocarbon resin emulsions.

FDA Status

Complies with 21CFR175.105

Applications

Blending with natural rubber latex, SBR latex, natural rubber/SBR latex blends and acrylic latexes

Typical Properties

| | |
|-----------------------------------|-------------|
| Total Solids | 56.0 ± 1.0 |
| Viscosity; LVF #3 @ 30 RPM @ 23°C | As Required |
| pH | 9.5 ± 1.0 |
| Softening Point | 79°C |
| Average Particle Size | <0.5 micron |

May 07

This product information is presented in good faith and is to the best of our knowledge, accurate. It is intended to be used as a guide and is not to be construed as a specification for products described herein. Dyna-Tech does not guarantee satisfactory results in any application from reliance upon this information and assumes no liability for any loss or damage arising out of its use. Dyna-Tech recommends that the user of our products thoroughly test them under end use conditions to assure that they meet the requirements of intended applications.