

DyTac 3240C

Emulsion – Pressure Sensitive General Purpose Removable Adhesive

DyTac 3240C is a solvent free rubber-resin emulsion, which upon drying produces a pressure sensitive film. It provides good adhesion to a variety of surfaces above 40°F, and is a candidate for evaluation in removable or repositionable label and tape applications. It is recommended for evaluation in removable labels for plastic dinnerware, plastic house-wares, videocassettes and other plastic surfaces.

FDA StatusComplies with 21CFR175.105

ApplicationsRemovable labels for smooth and lightly textured
plastics
Self wound removable tapes

Typical Properties

Total Solids	55.0 ± 1.0
Viscosity, as supplied	As Required
pH	9.3 ± 1.0
Weight per Gallon @ 23°C	8.3 lbs.
Minimum Application Temperature	40°F
Service Temperature Range	40°F to 160°F

Web:	60# High Gloss
Coatweight; lb./3000 ft ²	12.0
180° Peel, lb./in., Stainless Steel (1)	
30' dwell	0.8
24 hr. dwell	1.3
Shear, ½" x ½" x 500 gm. (2)	1.3 hr.

Samples were prepared by transfer coating and drying for 2½' @ 100°C

- (1) PSTC-101
- (2) PSTC-107

May 07