



ADHESIVES & COATINGS, INC
QURETECH®
TECHNICAL DATA SHEET

Country Club Road, PO Box 628
Grafton, WV 26354
800-847-7773
Fax; 304-265-5202
www.dyna-techadhesives.com
www.quiretech.com

Providing Advanced Water-based and Energy
Curable Coatings and Adhesives
For Over 25 Years.
Clean, Safe, Worker Friendly

DynaLoc 9525

HDPE Bottle Labeling Adhesive

DynaLoc 9525 is a bottle labeling adhesive intended primarily for adhering paper labels to plastic bottles. This high quality adhesive exhibits excellent adhesion to flame treated high-density polyethylene and is very clean machining with low odor.

FDA Status	Complies with 21CFR175.105
-------------------	----------------------------

Applications	HDPE, PP, PVC plastic bottle labeling
---------------------	---------------------------------------

Typical Properties

Total Solids ⁽¹⁾	61.0 ± 1.0%
Viscosity ⁽²⁾	40,000 – 60,000 cps
pH	8.0 ± 0.5
Weight per Gallon @ 23°C	9.0 ± 0.1 lbs.

Storage Life	3 months at room temperature
--------------	------------------------------

Application Method	In-labelers ie., Krones, Koyo
--------------------	-------------------------------

Viscosity variations available for machine specific requirements.

(1) Forced air oven 2 hours at 105° C

(2) Brookfield RVT, Spindle #7 @ 20 RPM at 25°C

May 07

This product information is presented in good faith and is to the best of our knowledge, accurate. It is intended to be used as a guide and is not to be construed as a specification for products described herein. Dyna-Tech does not guarantee satisfactory results in any application from reliance upon this information and assumes no liability for any loss or damage arising out of its use. Dyna-Tech recommends that the user of our products thoroughly test them under end use conditions to assure that they meet the requirements of intended applications