

DynaMelt 12

Hot Melt

DynaMelt 12 is a high tack, fast setting adhesive with excellent adhesion to a wide variety of board and paper stocks. DynaMelt 12 should also be evaluated in applications where low temperature adhesion is needed.

Applications

Case & Carton Sealing

Tray Forming

Glue Lap

Typical Properties

Type

Thermoplastic Resin

Color

Amber

Viscosity

1200 cps @ 350°F ± 100 cps

Speed of Set

Fast

Softening Point

235 ± 5°F

Heat Stability

Heat Stable, Will Not Char at Normal Operating Temperature for a Minimum of 100 Hours.

Application Temperature

350 – 375°F

Clean Up

Heat

Storage Life

Indefinite

Packaging

Slats, Packed in Double Wall Corrugated

Carton Lined with Polyethylene Protection

Machine

Extruder, Reservoir Pump, Wheel Types

This product information is presented in good faith and is to the best of our knowledge, accurate. It is intended to be used as a guide and is not to be construed as a specification for products described herein. Dyna-Tech does not guarantee satisfactory results in any application from reliance upon this information and assumes no liability for any loss or damage arising out of its use. Dyna-Tech recommends that the user of our products thoroughly test them under end use conditions to assure that they meet the requirements of intended applications.