

Providing Advanced Water-based and Energy

Curable Coatings and Adhesives

For Over 25 Years

Clean, Safe, Worker Friendly

# DynaMelt 22

## Hot Melt

---

DynaMelt 22 is a hot melt developed for use in the packaging industry. It is a flexible hot melt that will bond a variety of difficult stocks.

---

**FDA Status**

Complies with 21CFR175.105

**Applications**

Case &amp; Carton Sealing

---

### Typical Properties

Type	Thermoplastic Resin
Color	Lemon
Viscosity	850 ± 100 cps @ 350°F
Speed of Set	Medium for Better Penetration
Application Temperature	250 – 275°F
Heat Stability	Heat Stable, No Noticeable Adverse Effects After 100 Hours @ 350°F (177°C)
Clean Up	Easy, Heat & Scrapper
Storage Life	Indefinite

---

**Packaging**Slats, Packed in Double Wall Corrugated  
Carton Lined with Polyethylene Protection**Machine**

Muller Martini

May 07

This product information is presented in good faith and is to the best of our knowledge, accurate. It is intended to be used as a guide and is not to be construed as a specification for products described herein. Dyna-Tech does not guarantee satisfactory results in any application from reliance upon this information and assumes no liability for any loss or damage arising out of its use. Dyna-Tech recommends that the user of our products thoroughly test them under end use conditions to assure that they meet the requirements of intended applications.