



ADHESIVES & COATINGS, INC

QURETECH®

TECHNICAL DATA SHEET

Country Club Road, PO Box 628
Grafton, WV 26354
800-847-7773
Fax; 304-265-5202
www.dyna-techadhesives.com
www.quiretech.com

Providing Advanced Water-based and Energy
Curable Coatings and Adhesives
For Over 25 Years
Clean, Safe, Worker Friendly

DynaMelt 28

Hot Melt

DynaMelt 28 is a hot melt developed for use in the packaging industry. It is a high-speed carton and case sealing adhesive. DynaMelt 28 provides excellent heat resistance and adhesion for difficult to adhere to surfaces.

FDA Status

Complies with 21CFR175.105

Applications

Laminating Adhesive

Typical Properties

Type	Synthetic Resin
Color	Lemon
Viscosity	950 ± 100 cps @ 350°F
Speed of Set	Fast
Application Temperature	325 – 375°F
Heat Stability	Heat Stable, No Noticeable Adverse Effects After 100 Hours @ 350°F (177°C)
Clean Up	Easy, Heat & Scrapper
Storage Life	Indefinite

Packaging

Slats, Packed in Double Wall Corrugated
Carton Lined with Polyethylene Protection

Machine

Nordson LTI & Graco Units

May 07

This product information is presented in good faith and is to the best of our knowledge, accurate. It is intended to be used as a guide and is not to be construed as a specification for products described herein. Dyna-Tech does not guarantee satisfactory results in any application from reliance upon this information and assumes no liability for any loss or damage arising out of its use. Dyna-Tech recommends that the user of our products thoroughly test them under end use conditions to assure that they meet the requirements of intended applications.