

DynaMelt 30

Hot Melt

DynaMelt 30 is a translucent hot melt developed for use in the packaging industry. It is a tacky hot melt, which makes it useful for adhering difficult to bond substrates.

FDA Status

Complies with 21CFR175.105

Applications

Laminating Adhesive

Typical Properties

Type	Synthetic Resin
Color	Colorless
Viscosity	850 ± 50 cps @ 250°F
Softening Point	168 – 175°F
Application Temperature	250 – 325°F
Applicators	Extruder, Reservoir Pump, Wheel Systems
Heat Stability	Heat Stable, No Noticeable Adverse Effects After 100 Hours @ 350°F (177°C)
Clean Up	Easy, Heat & Scrapper
Storage Life	Indefinite

Packaging

Slats, Packed in Double Wall Corrugated Carton Lined with Polyethylene Protection

Machine

Nordson LTI & Graco Units

May 07

This product information is presented in good faith and is to the best of our knowledge, accurate. It is intended to be used as a guide and is not to be construed as a specification for products described herein. Dyna-Tech does not guarantee satisfactory results in any application from reliance upon this information and assumes no liability for any loss or damage arising out of its use. Dyna-Tech recommends that the user of our products thoroughly test them under end use conditions to assure that they meet the requirements of intended applications.