

# DynaMelt 33

## Hot Melt

DynaMelt 33 is a translucent hot melt developed for use in the packaging industry. It is recommended for use in freezer type applications where good cold crack is required.

**FDA Status**

Complies with 21CFR175.105

**Applications**

Case or Carton Sealing For Difficult Substrates

**Typical Properties**

Type	Synthetic Resin
Color	Lemon
Viscosity	2400 ± 100 cps @ 350°F
Speed of Set	Medium to Fast
Application Temperature	350 – 370°F
Applicators	Extruder, Reservoir Pump Wheel Systems
Heat Stability	Heat Stable, No Noticeable Adverse Effects After 100 Hours @ 350°F (177°C)
Application Temperature	250 – 275°F
Clean Up	Easy, Heat & Scrapper
Storage Life	Indefinite

**Packaging**

Slats, Packed in Double Wall Corrugated Carton Lined with Polyethylene Protection

**Machine**

Nordson LTI &amp; Graco Units

May 07

This product information is presented in good faith and is to the best of our knowledge, accurate. It is intended to be used as a guide and is not to be construed as a specification for products described herein. Dyna-Tech does not guarantee satisfactory results in any application from reliance upon this information and assumes no liability for any loss or damage arising out of its use. Dyna-Tech recommends that the user of our products thoroughly test them under end use conditions to assure that they meet the requirements of intended applications.