



ADHESIVES & COATINGS, INC
QURETECH®
TECHNICAL DATA SHEET

Country Club Road, PO Box 628
Grafton, WV 26354
800-847-7773
Fax; 304-265-5202
www.dyna-techadhesives.com
www.quiretech.com

Providing Advanced Water-based and Energy
Curable Coatings and Adhesives
For Over 25 Years.
Clean, Safe, Worker Friendly

FlexTac 7426

Packaging Adhesive

FlexTac 7426 is a high performance vinyl acetate copolymer based emulsion adhesive developed as a general purpose product for the packaging industry. FlexTac 7426 exhibits excellent adhesion to a wide variety of substrates and finds great utility as a general purpose folding box and folding carton adhesive. Features include excellent machining and easy clean-up properties along with superior adhesion to coated substrates as well as some films.

FDA Status	Complies with 21CFR175.105
-------------------	----------------------------

Applications	General purpose adhesive for the packaging industry
---------------------	---

Typical Properties

Total Solids (1)	55.0 ± 1.0 %
Viscosity ₁ (2)	2250 ± 250 cps
pH	4.5 ± 0.5
Weight per Gallon @ 25°C	8.8 ± 0.1 lbs.
Storage Life	3 months at room temperature
Application Method	Extrusion, wheel, rollers

Viscosity variations are available for custom built or machine manufacturer specific requirements. Tinted color variations as well as U.V tracer containing formulations also available.

(1) Forced air oven 2 hours at 105° C

(2) Brookfield RVT, Spindle #4 @ 20 RPM at 25°C

June 07

This product information is presented in good faith and is to the best of our knowledge, accurate. It is intended to be used as a guide and is not to be construed as a specification for products described herein. Dyna-Tech does not guarantee satisfactory results in any application from reliance upon this information and assumes no liability for any loss or damage arising out of its use. Dyna-Tech recommends that the user of our products thoroughly test them under end use conditions to assure that they meet the requirements of intended applications