



ADHESIVES & COATINGS, INC
QURETECH®
TECHNICAL DATA SHEET

Route 310 North, Country Club Road
PO Box 628, Grafton, WV 26354
304-265-5200, 800-847-7773
Fax: 304-265-5202
www.dyna-techadhesives.com

Providing Advanced Water-based and
Energy Curable Coatings and Adhesives
For Over 25 Years
Clean, Safe, Worker Friendly

**Flexibility To Meet Your Needs
Stability You Can Depend On**

DynaPrime WB-9324

DynaPrime 9324 is a water-based primer formulated for use as a barrier coat to aid in the prevention of plasticizer migration when coated onto vinyl facestocks. It is also recommended for use as a tie coat, as it provides a smooth print surface for most water based inks and coatings.

Physical Properties (as supplied)

Viscosity, as supplied	As Required
Total Solids:	41 ± 1.0%
PH	7.5 ± 1.0
Shelf life:	6 months from manufacture date

May 2010

This product information is presented in good faith and is to the best of our knowledge, accurate. It is intended to be used as a guide and is not to be construed as a specification for products described herein. Dyna-Tech does not guarantee satisfactory results in any application from reliance upon this information and assumes no liability for any loss or damage arising out of its use. Dyna-Tech recommends that the user of our products thoroughly test them under end use conditions to assure that they meet the requirements of intended applications. Statements and methods described herein are based upon the best information and practices known to Dyna-Tech Adhesives, Inc. However, procedures for applications mentioned are suggestions only and are not to be construed as representation or warranties as to performance results. Nor does Dyna-Tech Adhesives, Inc. warrant freedom from patent infringement in the use of any formula or process set forth herein. The user must test performance for acceptability using their conditions.