



ADHESIVES & COATINGS, INC
QURETECH®
 TECHNICAL DATA SHEET

Route 310 North, Country Club Road
 PO Box 628, Grafton, WV 26354
 304-265-5200, 800-847-7773
 Fax; 304-265-5202
 www.dyna-techadhesives.com

Providing Advanced Water-based and
 Energy Curable Coatings and Adhesives
 For Over 25 Years
 Clean, Safe, Worker Friendly

QureTech®

JRX-1187-B

**Flexibility To Meet Your Needs
 Stability You Can Depend On**

Description: Dip Lacquer for Hairbrush Tips

JRX-1187-B is designed to dip coat hairbrush tips to form a uniform tip. It is available in various colors.

FEATURES

<input type="checkbox"/> High Viscosity	<input type="checkbox"/> 100% Solids
<input type="checkbox"/> Process Ease	<input type="checkbox"/> Custom Colors Available

TECHNICAL INFORMATION:

Viscosity	34000 ó 48000 cps @ 25°C ó Brookfield viscometer
Appearance	Various Colors
Process	Dip coat
UV Light Source	Fusion UV Systems F300 -Høbulb, or Medium pressure mercury arc lamp, (300 watts/linear inch minimum)
Cure Speed	Linear line system, 30 ó 50 fpm x 1 lamp
Storage/Stability	Ambient temperature (12-25°C)
Handling	SEE MATERIAL SAFETY DATA SHEET

A/kjd

May 2010

This product information is presented in good faith and is to the best of our knowledge, accurate. It is intended to be used as a guide and is not to be construed as a specification for products described herein nor is it to be construed as a license to use the material in the infringement of patents. Dyna-Tech and QureTech do not guarantee satisfactory results in any application from reliance upon this information and assumes no liability for any loss or damage arising out of its use. Dyna-Tech and QureTech recommend that the user of our products thoroughly test them under end use conditions to assure that they meet the requirements of intended applications.